

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **E345000**  
Product name: **POLACRYL 345**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **POLYURETHANE VARNISH.**

#### 1.3. Details of the supplier of the safety data sheet

Name: **DGK-PELLACHROM**  
Full address: **RIZARI EDESSA**  
District and Country: **58200 EDESSA (GR)**  
**GREECE**  
Tel.: **+30 23810 26868**  
Fax: **+30 23810 27707**  
e-mail address of the competent person responsible for the Safety Data Sheet: **info@pellachrom.gr**

#### 1.4. Emergency telephone number

For urgent inquiries refer to: **+30 210-7793777**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

**H225** Highly flammable liquid and vapour.  
**H304** May be fatal if swallowed and enters airways.  
**H373** May cause damage to organs through prolonged or repeated exposure.

## SECTION 2. Hazards identification ... / &gt;&gt;

<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH208</b>	Contains: 2-BUTANONE OXIME May produce an allergic reaction.

## Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P261</b>	Avoid breathing dust / fume / gas / mist / vapours / spray.
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P301+P310</b>	IF SWALLOWED: immediately call a POISON CENTER / doctor / . . .
<b>P331</b>	Do NOT induce vomiting.
<b>P370+P378</b>	In case of fire: use . . . to extinguish.

<b>Contains:</b>	NAPHTHA (PETROL.) HYDROTREATED HEAVY NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY XYLENE (MIXTURE OF ISOMERS)
------------------	--

Product not intended for uses provided for by Dir. 2004/42/CE.

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

## 3.1. Substances

Information not relevant

## 3.2. Mixtures

## Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>NAPHTHA (PETROL.) HYDROTREATED HEAVY</b>		
CAS	64742-48-9 25 ≤ x < 50	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H336, Classification note according to Annex VI to the CLP Regulation: P
EC	265-150-3	
INDEX	649-327-00-6	
<b>XYLENE (MIXTURE OF ISOMERS)</b>		
CAS	1330-20-7 5 ≤ x < 10	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC	215-535-7	
INDEX	601-022-00-9	
<b>NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY</b>		
CAS	64742-82-1 2,5 ≤ x < 5,5	Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P
EC	265-185-4	
INDEX	649-330-00-2	
<b>2-BUTANONE OXIME</b>		
CAS	96-29-7 0 ≤ x < 1	Carc. 2 H351, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Sens. 1 H317
EC	202-496-6	
INDEX	616-014-00-0	
<b>CALCIUM BIS 2-ETHYLHEXANOATE</b>		
CAS	136-51-6 0 ≤ x < 1	Repr. 2 H361d, Eye Dam. 1 H318
EC	205-249-0	
INDEX		

**SECTION 3. Composition/information on ingredients ... />>****2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT**

CAS 22464-99-9 0,1 ≤ x &lt; 2 Repr. 2 H361d

EC 245-018-1

INDEX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**SECTION 6. Accidental release measures ... / >>****6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.  
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г
CZE	Česká Republika	Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2017

**NAPHTHA (PETROL.) HYDROTREATED HEAVY****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
NDS	POL	300		900	

**XYLENE (MIXTURE OF ISOMERS)****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN
TLV	CZE	200		400		SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	
NDS	POL	100				
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

### SECTION 8. Exposure controls/personal protection ... / >>

#### NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
NDS	POL	300		900	

#### 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		5		10	

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 434 mg/m3

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	colourless
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	> 35 °C
Boiling range	Not available
Flash point	< 23 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available

**SECTION 9. Physical and chemical properties ... / >>**

Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,96
Solubility	THINNER 135
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	60 K.U. (25 C)
Explosive properties	Not available
Oxidising properties	Not available

**9.2. Other information**

VOC (Directive 2010/75/EC) :	48,95 % - 469,92	g/litre
VOC (volatile carbon) :	48,30 % - 463,67	g/litre
Gloss	90(20) 99(60)	

**SECTION 10. Stability and reactivity**

**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**2-BUTANONE OXIME**

Decomposes under the effect of heat.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT**

SADT = 210°C/410°F.

**10.3. Possibility of hazardous reactions**

The vapours may also form explosive mixtures with the air.

**XYLENE (MIXTURE OF ISOMERS)**

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

**2-BUTANONE OXIME**

Reacts violently with: strong oxidising agents, acids.

Above the flash point (69°C/156°F), explosive mixtures can form with air.

**10.4. Conditions to avoid**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

**10.5. Incompatible materials**

**2-BUTANONE OXIME**

Incompatible with: oxidising substances, strong acids.

**10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

**2-BUTANONE OXIME**

May develop: nitric oxide, carbon oxides.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on toxicological effects

#### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

#### Interactive effects

XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

#### ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

>2000 mg/kg

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral)

3523 mg/kg Rat

LD50 (Dermal)

4350 mg/kg Rabbit

LC50 (Inhalation)

26 mg/l/4h Rat

CALCIUM BIS 2-ETHYLHEXANOATE

LD50 (Oral)

2043 mg/kg Rat - Fischer 344

LD50 (Dermal)

> 2000 mg/kg Rat - Wistar

2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

LD50 (Oral)

> 5000 mg/kg Rat - Sprague-Dawley

LD50 (Dermal)

> 2000 mg/kg Rat - Wistar

LC50 (Inhalation)

> 4,3 mg/l/4h Rat

2-BUTANONE OXIME

LD50 (Oral)

2400 mg/kg Rat

LD50 (Dermal)

> 1000 mg/kg Rabbit

LC50 (Inhalation)

20 mg/l/4h Rat

NAPHTHA (PETROL.) HYDROTREATED HEAVY

LD50 (Oral)

> 5000 mg/kg Rat

LD50 (Dermal)

> 2000 mg/kg Rabbit

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

LD50 (Oral)

> 5000 mg/kg Rat

LD50 (Dermal)

> 2000 mg/kg Rabbit

#### SKIN CORROSION / IRRITATION

**SECTION 11. Toxicological information ... / >>**

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

2-BUTANONE OXIME

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

**SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

**12.1. Toxicity**

**CALCIUM BIS 2-ETHYLHEXANOATE**

LC50 - for Fish	> 100 mg/l/96h Oryzias latipes
EC50 - for Crustacea	910 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	49,3 mg/l/72h Desmodesmus subspicatus

**2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT**

LC50 - for Fish	> 100 mg/l/96h Danio rerio
EC50 - for Algae / Aquatic Plants	49,3 mg/l/72h Desmodesmus subspicatus

**NAPHTHA (PETROL.) HYDROTREATED HEAVY**

LC50 - for Fish	8,2 mg/l/96h Pimephales promelas
EC50 - for Crustacea	4,5 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	3,1 mg/l/72h Pseudokirchnerella subcapitata

**NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY**

LC50 - for Fish	8,2 mg/l/96h Pimephales promelas
EC50 - for Crustacea	4,5 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	3,1 mg/l/72h Pseudokirchnerella subcapitata

**12.2. Persistence and degradability**



**SECTION 12. Ecological information ... / >>**

XYLENE (MIXTURE OF ISOMERS)	
Solubility in water	100 - 1000 mg/l
Degradability: information not available	
CALCIUM BIS 2-ETHYLHEXANOATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	
2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT	
Solubility in water	< 0,1 mg/l
Rapidly degradable	
2-BUTANONE OXIME	
Solubility in water	1000 - 10000 mg/l
Entirely degradable	
NAPHTHA (PETROL.) HYDROTREATED HEAVY	
Rapidly degradable	
NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY	
Rapidly degradable	

**12.3. Bioaccumulative potential**

XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: n-octanol/water	3,12
BCF	25,9
CALCIUM BIS 2-ETHYLHEXANOATE	
Partition coefficient: n-octanol/water	2,96
2-BUTANONE OXIME	
Partition coefficient: n-octanol/water	0,63
BCF	0,5

**12.4. Mobility in soil**

XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: soil/water	2,73
2-BUTANONE OXIME	
Partition coefficient: soil/water	0,55
NAPHTHA (PETROL.) HYDROTREATED HEAVY	
Partition coefficient: soil/water	1,78
NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY	
Partition coefficient: soil/water	1,78

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number**

ADR / RID, IMDG, IATA: 1263

**14.2. UN proper shipping name**ADR / RID: PAINT or PAINT RELATED MATERIAL  
IMDG: PAINT or PAINT RELATED MATERIAL  
IATA: PAINT or PAINT RELATED MATERIAL**14.3. Transport hazard class(es)**

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

**14.5. Environmental hazards**ADR / RID: NO  
IMDG: NO  
IATA: NO**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 33 Special Provision: 640C	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo: Pass.: Special Instructions:	Maximum quantity: 60 L Maximum quantity: 5 L A3, A72, A192	Packaging instructions: 364 Packaging instructions: 353

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

**SECTION 15. Regulatory information ... / >>**

Substances subject to the Rotterdam Convention:  
None

Substances subject to the Stockholm Convention:  
None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Interior/exterior trim varnishes and woodstains.

**15.2. Chemical safety assessment**

No chemical safety assessment has been processed for the mixture and the substances it contains.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Carc. 2</b>	Carcinogenicity, category 2
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H351</b>	Suspected of causing cancer.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%

**SECTION 16. Other information ... / >>**

- LD50: Lethal dose 50%- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## Changes to previous review:

The following sections were modified:

09.