

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **G990999**
Product name: **POOLGLOSS COMPONENT B**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Not available**

1.3. Details of the supplier of the safety data sheet

Name: **DGK-PELLACHROM**
Full address: **RIZARI EDESSA**
District and Country: **58200 EDESSA (GR)**
GREECE
Tel. **+30 23810 26868**
Fax **+30 23810 27707**

e-mail address of the competent person responsible for the Safety Data Sheet: **info@pellachrom.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **+30 210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Acute toxicity, category 4	H332	Harmful if inhaled.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Respiratory sensitization, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

SECTION 2. Hazards identification ... / >>

Hazard statements:

H225	Highly flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
EUH204	Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER / doctor / . . .
P331	Do NOT induce vomiting.
P342+P311	If experiencing respiratory symptoms: call a POISON CENTER / doctor / . . .

Contains:	TOLUENE XYLENE (MIXTURE OF ISOMERS) NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY ALIPHATIC POLYISOCYANATE
------------------	---

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
ALIPHATIC POLYISOCYANATE		
CAS	28182-81-2 25 ≤ x < 50	Acute Tox. 4 H332, Resp. Sens. 1 H334, Skin Sens. 1 H317
EC		
INDEX		
XYLENE (MIXTURE OF ISOMERS)		
CAS	1330-20-7 25 ≤ x < 50	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC	215-535-7	
INDEX	601-022-00-9	
TOLUENE		
CAS	108-88-3 20 ≤ x < 35	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336
EC	203-625-9	
INDEX	601-021-00-3	
2-METHOXY-1-METHYLETHYL ACETATE		
CAS	108-65-6 5 ≤ x < 10	Flam. Liq. 3 H226
EC	203-603-9	
INDEX	607-195-00-7	
NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY		
CAS	64742-82-1 0 ≤ x < 2,5	Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P
EC	265-185-4	

SECTION 3. Composition/information on ingredients ... />>

INDEX 649-330-00-2

ETHYLBENZENE

CAS 100-41-4 0,1 ≤ x < 2

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373

EC 202-849-4

INDEX 601-023-00-4

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

SECTION 6. Accidental release measures ... / >>

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
 Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г
CZE	Česká Republika	Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2017

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN
TLV	CZE	200		400		SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	
NDS	POL	100				
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

SECTION 8. Exposure controls/personal protection ... / >>
TOLUENE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	150		300		
TLV	CZE	200		500		SKIN
VLEP	FRA	76,8	20	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
TLV	GRC	192	50	384	100	
NDS	POL	100		200		
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			

2-METHOXY-1-METHYLETHYL ACETATE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275		550		SKIN
TLV	CZE	270		550		SKIN
VLEP	FRA	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	
TLV	GRC	275	50	550	100	
NDS	POL	260		520		
OEL	EU	275	50	550	100	SKIN

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
NDS	POL	300		900		

ETHYLBENZENE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
TLV	CZE	200		500		SKIN
VLEP	FRA	88,4	20	442	100	SKIN
WEL	GBR	441	100	552	125	SKIN
TLV	GRC	435	100	545	125	
NDS	POL	200		400		
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 138 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

SECTION 8. Exposure controls/personal protection ... / >>

EYE PROTECTION Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	colourless
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	> 35 °C
Boiling range	Not available
Flash point	< 23 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,97
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2010/75/EC) :	58,45 % - 569,30	g/litre
VOC (volatile carbon) :	54,63 % - 532,12	g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE

Avoid exposure to: light.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

SECTION 10. Stability and reactivity ... / >>**10.3. Possibility of hazardous reactions**

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials**2-METHOXY-1-METHYLETHYL ACETATE**

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information**2-METHOXY-1-METHYLETHYL ACETATE**

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure**XYLENE (MIXTURE OF ISOMERS)**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SECTION 11. Toxicological information ... / >>**XYLENE (MIXTURE OF ISOMERS)**

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispes). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects**XYLENE (MIXTURE OF ISOMERS)**

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	10,86 mg/l
LD50 (Oral) of the mixture:	Not classified (no significant component)
LD50 (Dermal) of the mixture:	>2000 mg/kg

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral)	3523 mg/kg Rat
LD50 (Dermal)	4350 mg/kg Rabbit
LC50 (Inhalation)	26 mg/l/4h Rat

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Oral)	8530 mg/kg Rat
LD50 (Dermal)	> 5000 mg/kg Rat

TOLUENE

LD50 (Oral)	5580 mg/kg Rat
LD50 (Dermal)	12124 mg/kg Rabbit
LC50 (Inhalation)	28,1 mg/l/4h Rat

ETHYLBENZENE

LD50 (Oral)	3500 mg/kg Rat
LD50 (Dermal)	15354 mg/kg Rabbit
LC50 (Inhalation)	17,2 mg/l/4h Rat

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

LD50 (Oral)	> 5000 mg/kg Rat
LD50 (Dermal)	> 2000 mg/kg Rabbit

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

SECTION 11. Toxicological information ... / >>

Sensitising for the respiratory system

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation
May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity**NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY**

LC50 - for Fish	8,2 mg/l/96h Pimephales promelas
EC50 - for Crustacea	4,5 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	3,1 mg/l/72h Pseudokirchnerella subcapitata

12.2. Persistence and degradability**XYLENE (MIXTURE OF ISOMERS)**

Solubility in water	100 - 1000 mg/l
Degradability: information not available	

ALIPHATIC POLYISOCYANATE

Solubility in water	0,1 - 100 mg/l
Degradability: information not available	

2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water	> 10000 mg/l
Rapidly degradable	

SECTION 12. Ecological information ... / >>

TOLUENE
Solubility in water 100 - 1000 mg/l
Rapidly degradable

ETHYLBENZENE
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY
Rapidly degradable

12.3. Bioaccumulative potential

XYLENE (MIXTURE OF ISOMERS)
Partition coefficient: n-octanol/water 3,12
BCF 25,9

ALIPHATIC POLYISOCYANATE
Partition coefficient: n-octanol/water 5,54
BCF 367,7

2-METHOXY-1-METHYLETHYL ACETATE
Partition coefficient: n-octanol/water 1,2

TOLUENE
Partition coefficient: n-octanol/water 2,73
BCF 90

ETHYLBENZENE
Partition coefficient: n-octanol/water 3,6

12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)
Partition coefficient: soil/water 2,73

ALIPHATIC POLYISOCYANATE
Partition coefficient: soil/water 7,3

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY
Partition coefficient: soil/water 1,78

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, IATA: 1263

SECTION 14. Transport information ... / >>**14.2. UN proper shipping name**

ADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33 Special Provision: 640C	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo: Pass.: Special Instructions:	Maximum quantity: 60 L Maximum quantity: 5 L A3, A72, A192	Packaging instructions: 364 Packaging instructions: 353

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 48 TOLUENE

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

SECTION 15. Regulatory information ... / >>

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH204	Contains isocyanates. May produce an allergic reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

SECTION 16. Other information ... / >>

- TWA STEL: Short-term exposure limit- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 06 / 07 / 09 / 10 / 11 / 12 / 14 / 15.