# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 ΕN

Page n. 1 / 9

# **Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: A037002

Product name PROFESSIONAL ACRYLIC RED N.02

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use ACRYLIC WALL PAINT.

1.3. Details of the supplier of the safety data sheet

Name DGK-PELLACHROM Full address RIZARI EDESSA

District and Country 58200 EDESSA (GR)

GREECE
Tel. +30 23810 26868
Fax +30 23810 27707

 $\mbox{e-mail}$  address of the competent person

responsible for the Safety Data Sheet info@pellachrom.gr

1.4. Emergency telephone number

For urgent inquiries refer to +30 210-7793777

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication: --

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

**EUH208** Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one

(3:1)

1,2-Benzoisothiazol-3(2H)-one

May produce an allergic reaction.

Precautionary statements: --

VOC (Directive 2004/42/EC):

Coatings for exterior walls of mineral substrate.

VOC given in g/litre of product in a ready-to-use condition : 11,56
Limit value: 40,00

- Thinned with: 10,00 % WATER

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

ΕN



# **DGK-PELLACHROM**

# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 2 / 9

## **SECTION 3. Composition/information on ingredients**

#### 3.1. Substances

Information not relevant

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

1,2-Benzoisothiazol-3(2H)-one

CAS 2634-33-5 0 ≤ x < 0,05 Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC 220-120-9 INDEX 613-088-00-6

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)

CAS 55965-84-9 0 ≤ x < 0,0015 Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Skin Corr. 1B H314,

Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1,

Aquatic Chronic 1 H410 M=1

EC

INDEX 613-167-00-5

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

# 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of

ΕN



# **DGK-PELLACHROM**

# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 3 / 9

contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

#### **SECTION 8. Exposure controls/personal protection**

## 8.1. Control parameters

TLV of solvent mixture: 1 mg/m3

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION** 

Wear airtight protective goggles (see standard EN 166).



# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 4 / 9

#### SECTION 8. Exposure controls/personal protection .../>>

RESPIRATORY PROTECTIONIf the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance liquid
Colour red
Odour characteristic

Odour threshold Not available 8 1 Melting point / freezing point Not available Initial boiling point 100 °C Boiling range Not available Flash point °C 60 Not available **Evaporation Rate** Flammability of solids and gases Not available

Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure 23 mmHa Vapour density Not available Relative density 1,53 WATER Solubility Partition coefficient: n-octanol/water Not available Not available Auto-ignition temperature Not available Decomposition temperature 120+10 KU Viscosity Not available

#### 9.2. Other information

Explosive properties Oxidising properties

VOC (Directive 2004/42/EC) : 0,90 % - 13,77 g/litre Gloss 2,6 (60) 29 (85)

Not available

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### **CALCIUM CARBONATE**

Decomposes at temperatures above 800°C/1472°F.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

# PELLACHROM

# **DGK-PELLACHROM**

# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 5 / 9

#### SECTION 10. Stability and reactivity .../>>

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

**CALCIUM CARBONATE** Incompatible with: acids.

#### 10.6. Hazardous decomposition products

**CALCIUM CARBONATE** 

May develop: calcium oxides, carbon oxides.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### **ACUTE TOXICITY**

Not classified (no significant component) LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: LD50 (Dermal) of the mixture: Not classified (no significant component)

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1)

LD50 (Oral) 481 mg/kg > 1,008 mg/kg LD50 (Dermal) LC50 (Inhalation) 1,23 mg/l/4h

**CALCIUM CARBONATE** 

LD50 (Oral) 6450 mg/kg Rat

TITANIUM DIOXIDE

LD50 (Oral) > 10000 mg/kg Rat

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### **SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

### **RESPIRATORY OR SKIN SENSITISATION**

May produce an allergic reaction.

Contains:

@ EPY 9.6.6 - SDS 1004.9

ΕN

# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 6 / 9

# SECTION 11. Toxicological information .../>>

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one (3:1) 1,2-Benzoisothiazol-3(2H)-one

#### **GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### **STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

## 12.1. Toxicity

Information not available

#### 12.2. Persistence and degradability

**CALCIUM CARBONATE** 

Solubility in water 0,1 - 100 mg/l

**TALC** 

Solubility in water < 0,1 mg/l

TITANIUM DIOXIDE

Solubility in water < 0,001 mg/l

Degradability: information not available

#### 12.3. Bioaccumulative potential

Information not available

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

@EPY 9.6.6 - SDS 1004.9

ΕN



# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 7 / 9

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number

Not applicable

#### 14.2. UN proper shipping name

Not applicable

#### 14.3. Transport hazard class(es)

Not applicable

#### 14.4. Packing group

Not applicable

#### 14.5. Environmental hazards

Not applicable

#### 14.6. Special precautions for user

Not applicable

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

# **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 None

#### Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

#### Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls



# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 8 / 9

#### **SECTION 15. Regulatory information** .../>>

Information not available

VOC (Directive 2004/42/EC):

Coatings for exterior walls of mineral substrate.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2
Acute toxicity, category 2
Acute Tox. 3
Acute toxicity, category 3
Acute Tox. 4
Skin Corr. 1B
Skin corrosion, category 1B
Eye Dam. 1
Skin Irrit. 2
Skin irritation, category 2
Skin Sens. 1
Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H330 Fatal if inhaled.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

**H318** Causes serious eye damage.

H315 Causes skin irritation.

**H317** May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 EUH210 Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).



# PROFESSIONAL ACRYLIC RED N.02

Revision nr.2 Dated 03/02/2019 Printed on 03/02/2019 Page n. 9 / 9

#### **SECTION 16. Other information** .../>>

GENERAL BIBLIOGRAPHY1. Regulation (EC) 1907/2006 (REACH) of the European Parliament

- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.