

BASIC TOUCH

basic emulsion paint

- easily dispersed
- great tinting power
- great resistance to UV-rays and time ageing

BASIC TOUCH is used for tinting the white shade in order to create new shades with emulsion and acrylic paints. It is easily dispersed and has great tinting power. Due to its special pigments, it provides unalterable shades with great resistance to alkali, UV-rays and time ageing.



COVERAGE	-m ² /L
FINISH	MATT
THINNING	0% WATER
DRYING TIMES	- hours *
RECOATING TIMES	- hours *
RECOMMENDED NUMBER OF COATS	- coats
TOOLS	roller, brush or spray airless

* Lower temperatures or higher relative humidity will prolong drying and recoating times.

TECHNICAL CHARACTERISTICS

TYPE	COPOLYMER PVA-VeοVα	
SPECIFIC GRAVITY	ΕΤΟΙΜΕΣ ΑΠΟΧΡΩΣΕΙΣ	1.20 ±0,05gr/cm ³
SOLIDS w/w (ISO 3251-03)		60±2 % *
SOLIDS w/v (ISO 3233-98)		39±3 % *
VISCOSITY (ASTM D 562-05 @ 25°C)		KU 110±10 *
pH		8.40±0.3
HIDING POWER (ISO 3905)		96% 150µm wet film**
APPLICATION TEMPERATURE		min 5°C-max 30°C

*differs depending on the shade.

REGULATION 2004/42/CE

Does not fall into the categories stipulated in Regulation 2004/42/EC.

TECHNICAL DATA SHEET

EDITION: FEBRUARY 2019

H040 | **BASIC TOUCH**

REPLACES ALL EARLIER VERSIONS

COLORANTS

H

SURFACE PREPARATION

Carefully prepare surface to obtain good results. Surface must be clean, dry and free from loose or flaking material, dust, oils and salting.

INTENDED USE

	PLASTER
	CONCRETE / CEMENT
	GYPSPUM BOARD / PUTTY
	WOOD

APPLICATION

- ▶ Add in the paint pot the desired quantities of the BASIC TOUCH shades you wish. Stir well to properly mix the colors with white and obtain a homogeneous mix.
- ▶ Stir well before use and during application.
- ▶ Allow newly poured concrete to cure for 30 days, then prime with FERM (H₂O) before painting with DECONYL MATT.

USEFUL INFORMATION

- ▶ Allow 30-40 days before coating new plaster or concrete.
- ▶ Do not paint when ambient temperature is below 5°C or over 35°C.
- ▶ Allow 20-30 days before washing newly painted surfaces.

PACKAGING

- ▶ Available in 8 ready-made shades. Containers of 150ml, 350ml and 750ml.

STORAGE

2 years if unopened and stored under normal storage conditions. Once opened, seal well and store in a closed place at room temperature between 5-30°C. Keep tightly closed after application for future use. Store in a cool place. Protect against freeze and direct sunlight.

CLEAN-UP / DISPOSAL

Keep your tools wet inside the can when not painting. Rub excess paint off your tools on the side of the can after paint application. Clean tools with hot water and soap immediately after use. Do not empty washing liquids into the water table. Always handle empty containers and product carefully. Do not pour leftover product down the drain. Strictly follow local, regional, national regulations and

legislation on the disposal of products and empty containers.

HEALTH & SAFETY

Read carefully the safety instructions on the label. For more information, consult the Safety Data Sheet.



D.G.K. PELLACHROM RIZARI AREA-EDESSA-58200, GREECE

T: +30 23810 26868 **F:** +30 23810 27707

www.pellachrom.gr | info@pellachrom.gr

|Page 2 of 2|

PELLACHROM
DECORATIVE & MARINE COATINGS